



CUSHMAN®

TRUCKSTER XD



CLASS-LEADING POWER AND PRODUCTIVITY.

The Truckster XD makes quick work of your hardest jobs with the industry's largest standard payload and your choice of Kubota petrol or diesel engines. A highly versatile bed - manufactured with strong heavy gauge steel, integrated stake pockets and tie-downs - makes effortless hauling for your heaviest loads. Built to operate in the toughest of conditions with the industry's highest approach angle, and largest ergonomic operator platform, your crew can count on the Truckster XD to handle the strenuous tasks with ease.

LET'S WORK.

32.5 HP
PETROL ENGINE

OR

24.8 HP
DIESEL ENGINE

668 L
BED VOLUME

1,610 KG
TOTAL PAYLOAD



CUSHMAN® TRUCKSTER XD



OPTIONS & ACCESSORIES

- 168 cm (66") Box
- 2" Receiver Hitch
- Canopy (two or four post ROPS)
- Four-post ROPS Premium Suspension Seat (operator and passenger)
- Hi/Lo Hydraulics with Remote Ports
- Hydraulic PTO
- Throttle Control
- Turn Signals
- Cab
- Doors
- Heater
- Auto Tailgate
- Fifth-wheel BallHitch Including Electric Brake Controller
- Core Harvester
- Top Dresser
- 1500 Vicon Spreader
- Quick Aerator
- Implement Lift
- Mirrors Left and Right
- Windshield for Four-post ROPS Storage Accessory
- Work Light Kit
- Backup Alarm
- Exhaust Spark Arrestor
- Fifth-gear Lock Out



COVERED WITH THE 2-YEAR CUSHMAN CARE TOTAL PROTECTION WARRANTY

PETROL

DIESEL

BODY & CHASSIS	
FRAME	Powder Coated Steel
BODY & FINISH	Injection Molded
STANDARD COLOUR	Orange or Green
DIMENSIONS	
OVERALL LENGTH	132 in. w/o bed, 136 w/ bed
OVERALL WIDTH	165 cm (65 in)
OVERALL HEIGHT	198 cm (78 in)
WHEEL BASE	165 cm (65 in)
FRONT WHEEL TRACK	124 cm (49 in)
REAR WHEEL TRACK	132 cm (52 in)
GROUND CLEARANCE	16 cm (6.5 in)
CARGO BOX CAPACITY	0.7 m ³ (23.6 cu ft)
POWER	
POWER SOURCE	32.5 HP Kubota Petrol Engine
VALVE TRAIN	3-Cylinder, 4-Cycle Liquid Cooled EFI
HORSEPOWER	32.5 HP
BATTERY (QTY/TYPER)	12 Volt Battery
KEY OR PEDAL START	Key Start
COOLING SYSTEM	Liquid Cooled
FUEL CAPACITY	26.5 L (7.0 gal) unleaded
DRIVE TRAIN	Engine Shaft Direct Drive
GEAR SELECTION	Five Speed Manual
REAR AXLE RATIO	High 14.2:1 / Low 45:1
PERFORMANCE	
SEATING CAPACITY	2-Person
VEHICLE LOAD CAPACITY	1,610 kg (3,550 LBS)
SPEED	23 mph
TOWING CAPACITY	998 kg, 1587 kg (2,200 lbs, 3,500) w/ trailer brakes
STEERING & SUSPENSION	
STEERING	Hydrostatic Power
FRONT/REAR SUSPENSION	Solid axle w/ leaf springs & shock absorbers
SERVICE BRAKE	Heavy-Duty Hydraulic Four Wheel Disk Brakes w/ 10.7 in. Disk
PARKING BRAKE	Hand Lever Actuated Disk Brakes on Rear Wheels
FRONT TYRES	23 x 10.5 - 14 6-ply Ribbed (2WD) / 14 6-ply Treaded (4WD)
REAR TYRES	26 x 12 - 14 6-ply Ultra Chevron Tread