



CUSHMAN®



# REFRESHER OASIS

DRIVING PROFITS WITH UNMATCHED CAPACITY.

The Cushman® Refresher Oasis raises the bar for large-volume refreshment vehicles with an industry-leading 500-can capacity, meaning your workers will spend less time refilling the vehicle and more time generating revenue. With the industry's only 72-volt AC electric drivetrain the Oasis delivers unmatched energy efficiency, power and silent performance that supports every round to make those long summer days a breeze.

LET'S WORK.

**72V**  
AC  
ELECTRIC  
OR

**13.5HP**  
KAWASAKI®  
PETROL

**1.12**  
M<sup>sq</sup>  
COUNTER

**4**  
BEVERAGE  
COMPARTMENTS

**900 L**  
DRY STORAGE

**500**  
CAN  
CAPACITY





# CUSHMAN® REFRESHER OASIS



BEVERAGE COMPARTMENT



MERCHANDISE CABINET



CUSTOMER FRIENDLY WRAP-AROUND COUNTER

## OPTIONS & ACCESSORIES

- Rubbish/Recycle Bins
- Aluminum Canopy Frame
- Colour Options Available for Canopy, Unit & Vehicle
- 3.0 Litre Airpots (2)
- Reversible Airpot Holder
- Humidor
- Consumable Ice Bin
- NSF Rated Ice Sink
- Unique Drainage
- Wheel Covers
- Turf Tyres
- 12-volt Outlet
- USB Outlet
- LED Headlights
- Glove Box Door and Shelf
- Brake Lights

	ELECTRIC	PETROL
<b>BODY &amp; CHASSIS</b>		
<b>FRAME</b>	Welded Steel with E-Shield e-coat plus DuraShield Powder Coat	Welded Steel with E-Shield e-coat plus DuraShield Powder Coat
<b>BODY &amp; FINISH</b>	Injection Molded TPO, Painted (front)	Injection Molded TPO, Painted (front)
<b>STANDARD COLOUR</b>	Forest Green	Forest Green
<b>DIMENSIONS</b>		
<b>OVERALL LENGTH</b>	297.18 cm (117.0 in)	297.18 cm (117.0 in)
<b>OVERALL WIDTH</b>	129.032 cm (50.8 in)	129.032 cm (50.8 in)
<b>OVERALL HEIGHT (NO CANOPY)</b>	120.40 cm (47.4)	120.40 cm (47.4)
<b>OVERALL HEIGHT (WITH CANOPY)</b>	186.18 cm (73.3 in)	186.18 cm (73.3 in)
<b>WHEEL BASE</b>	193.04 cm (76 in)	193.04 cm (76 in)
<b>FRONT WHEEL TRACK</b>	88.90 cm (35 in)	88.90 cm (35 in)
<b>REAR WHEEL TRACK</b>	97.79 cm (38.5 in)	97.79 cm (38.5 in)
<b>GROUND CLEARANCE</b>	11.43 cm (4.5 in)	11.43 cm (4.5 in)
<b>REFRESHER UNIT MATERIAL AND FINISH</b>	5000 Series Aluminum - Super Durable TGIC Polyester Powder Coating	5000 Series Aluminum - Super Durable TGIC Polyester Powder Coating
<b>POWER</b>		
<b>POWER SOURCE</b>	72-Volts	4 Cycle 24.5 cu in (401 cc)
<b>MOTOR TYPE</b>	AC Induction	N/A
<b>VALVE TRAIN</b>	N/A	Single Cylinder OHV
<b>HORSEPOWER (KW)</b>	22.4HP (16.7 kW) - Measured at Peak Torque	13.5 hp (10.1 kW) Exceeds SAE J1940 Standard
<b>ELECTRICAL SYSTEM</b>	72 Volt	Starter/Generator, Solid-State Regulator
<b>BATTERY (QTY/TYPER)</b>	Nine 8-Volt Deep Cycle	One 12 Volt Maintenance Free
<b>BATTERY CHARGER</b>	900 Watt 72V DC	
<b>KEY OR PEDAL START</b>	Pedal	Pedal
<b>AIR CLEANER</b>	N/A	Industrial Rated Dry Filter
<b>LUBRICATION</b>	N/A	Pressurised Oil System
<b>OIL FILTER</b>	N/A	Spin-On
<b>COOLING SYSTEM</b>	Motor Shaft Direct Drive	Air Cooled
<b>FUEL CAPACITY</b>	N/A	22.7 L (6.0 Gallon) tank
<b>DRIVE TRAIN</b>	Motor Shaft Direct Drive	Continuously Variable Transmission (CVT)
<b>TRANSAXLE</b>	Differential with Helical Gears	Differential with Helical Gears
<b>GEAR SELECTION</b>	Forward-Neutral-Reverse	Forward-Reverse
<b>REAR AXLE RATIO</b>	17:1	16.53:1 (Forward) 16.81:1 (Reverse)
<b>PERFORMANCE</b>		
<b>SEATING CAPACITY</b>	2 Person	2 Person
<b>DRY WEIGHT (w/o batteries)</b>	501.22 kg (1105 lb)	514.83 kg (1135 lb)
<b>CURB WEIGHT</b>	757.50 kg (1670 lb)	532.971 kg (1175 lb)
<b>VEHICLE LOAD CAPACITY</b>	483 kg (1066 lb)	483 kg (1066 lb)
<b>OUTSIDE CLEARANCE CIRCLE</b>	6.5 m (21.5 ft)	6.5 m (21.5 ft)
<b>SPEED</b>	11 mph ± 0.5 mph (17.7 kph ± 0.8 kph)	11 mph ± 0.5 mph (17.7 kph ± 0.8 kph)
<b>STEERING &amp; SUSPENSION</b>		
<b>STEERING</b>	Self-Compensating Rack and Pinion	
<b>FRONT/REAR SUSPENSION</b>	Leaf Springs with Hydraulic Shock Absorbers	
<b>SERVICE BRAKE</b>	Rear Wheel Mechanical Self-adjusting Drum	
<b>PARKING BRAKE</b>	Self-compensating, Single Point Engagement	
<b>TYRES</b>	18 x 8.5-8	